

DINTEX® FT1880S-PE

Features

- Translucent matte
- Anti-static
- Excellent hydrolysis resistance
- Oeko-Tex Standard 100 approval
- Smooth and soft touch
- Not sticky after repeat machine wash and heat-dry

Physical Properties

| *Properties | Method | Unit | **Value | Note |
|------------------|---|-------------------------|-------------------|--|
| Thickness | | mm | 0.015 | Standard Packing 1900 yd / roll |
| Width | | mm inch | 1524 60 | |
| Color | | | Translucent matte | |
| M.V.T. | ASTM E96-93BW 23°C/50%R.H. | g/m ² x24hrs | 12000 | |
| M.V.T. | JIS L1099-1993 A-1(CaCl ₂)40 °C 90% R.H. | g/m ² x24hrs | 4500 | |
| W.P.R. | JIS L1092-1998 B Method | mmH ₂ O | 10000 | |
| Specific Gravity | ASTM D792 | | 1.20 | |
| Elongation | ASTM D882 | % | 250 | |
| PE Carrier | | | Yes | |

**Actual results may yield up to ±15%.

*Data provided are used solely for references only, and are not guaranteed statements.



DING ZING CHEMICAL PRODUCTS CO., LTD.

SINCE 1981

http://www.dingzing.com e-mail: film@dingzing.com.tw Tel: +886 - 7 - 8070166
No.8-1, Pei-Lin Rd. Hsiao-Kang Dist., Kaohsiung, Taiwan Fax: +886 - 7 - 8071616