

## Ding Zing® Film FS26V0-PE

### Features

- Polyurethane polyester base
- UL 94V-0 grade
- Non-halogenated
- Flame retardant hot melt film
- Eco-friendly
- Suitable for various laminations

### Physical Properties

*Properties	Unit	Method	Direction	**Value	Note
Hardness	Shore A	ASTM D2240		92 ±3	
Specific Gravity		ASTM D792		1.13	
Tensile Strength	Kg/cm <sup>2</sup>	ASTM D882	MD	219	
			CD	242	
300% Modulus	Kg/cm <sup>2</sup>	ASTM D882	MD	69	
			CD	66	
Elongation	%	ASTM D882	MD	730	
			CD	769	
Tear Strength	Kg/cm	ASTM D624 (Die C)	MD	96	
			CD	90	
Film Melting Point	°C			60	

\*\*Actual results may yield up to ±15%.

\*Data provided are used solely for references only, and are not guaranteed statements.



**DING ZING CHEMICAL PRODUCTS CO., LTD.**

SINCE 1981

http://www.dingzing.com e-mail: film@dingzing.com.tw Tel: +886 - 7 - 8070166  
No.8-1, Pei-Lin Rd. Hsiao-Kang Dist., Kaohsiung, Taiwan Fax: +886 - 7 - 8071616