

## DINTEX® FT1881S-PE

### Features

- White matte
- Smooth and soft touch
- Excellent hydrolysis resistance
- Oeko-Tex Standard 100 approval
- Not sticky after repeat machine wash and heat-dry
- Anti-static

### Physical Properties

*Properties	Method	Unit	**Value	Note
Thickness		mm	0.020	
Width		mm inch	1524 60	
Color			White matte	
M.V.T.	ASTM E96-93BW 23°C/50%R.H.	g/m <sup>2</sup> x24hrs	12000	
M.V.T.	JIS L1099-1993 A1(CaCl <sub>2</sub> )40 °C 90% R.H.	g/m <sup>2</sup> x24hrs	4000	
W.P.R.	JIS L1092-1998 B Method	mmH <sub>2</sub> O	10000	
Specific Gravity	ASTM D792		1.23	
Elongation	ASTM D882	%	300	
PE Carrier			Yes	

\*\*Actual results may yield up to ±15%.

\*Data provided are used solely for references only, and are not guaranteed statements.



**DING ZING CHEMICAL PRODUCTS CO., LTD.**

SINCE 1981

http://www.dingzing.com e-mail: film@dingzing.com.tw Tel: +886 - 7 - 8070166  
No.8-1, Pei-Lin Rd. Hsiao-Kang Dist., Kaohsiung, Taiwan Fax: +886 - 7 - 8071616