

Ding Zing[®] Film FS3285

Features

- Polyurethane polyester base
- High temperature resistance
- Excellent hydrolysis resistance
- Strong physical properties
- Good UV stability

Physical Properties

*Properties	Unit	Method	Direction	**Value	Note
Hardness	Shore A	ASTM D2240		85 ±3	
Specific Gravity		ASTM D792		1.19	
Tensile Strength	Kg/cm ²	ASTM D882	MD	453	
			CD	399	
Elongation	%	ASTM D882	MD	524	
			CD	504	
300% Modulus	Kg/cm ²	ASTM D882	MD	122	
			CD	119	
Tear Strength	Kg/cm	ASTM D624	MD	87	
			CD	87	
Film Melting Point	°C			161	
UV stability	Grade	ASTM D1148		4	
Melting Flow Index	g/10min	ASTM D1238		99	

**Actual results may yield up to ±15%.

*Data provided are used solely for references only, and are not guaranteed statements.



DING ZING CHEMICAL PRODUCTS CO., LTD.

SINCE 1981

http://www.dingzing.com e-mail: film@dingzing.com.tw Tel: +886 - 7 - 8070166
No.8-1, Pei-Lin Rd. Hsiao-Kang Dist., Kaohsiung, Taiwan Fax: +886 - 7 - 8071616