

## Ding Zing® Film FT1080

### Features

- Polyurethane polyether base
- Good low temperature flexibility
- Excellent hydrolysis resistance
- Soft touch
- Outstanding waterproof characteristic good M.V.T. rate
- Hydrophilic structure

### Physical Properties

*Properties	Unit	Method	Direction	**Value	Note
Hardness	Shore A	ASTM D2240		80 ±3	
Specific Gravity		ASTM D792		1.21	
Tensile Strength	Kg/cm <sup>2</sup>	ASTM D412	MD CD	215 210	
Elongation	%	ASTM D412	MD CD	700 705	
300% Modulus	Kg/cm <sup>2</sup>	ASTM D412	MD CD	70 70	
Tear Strength	Kg/cm	ASTM D624	MD CD	110 105	
Film Melting Point	°C			140	
UV stability	Grade	ASTM D1148		2	

\*\*Actual results may yield up to ±15%.

\*Data provided are used solely for references only, and are not guaranteed statements.



**DING ZING CHEMICAL PRODUCTS CO., LTD.**

SINCE 1981

http://www.dingzing.com e-mail: film@dingzing.com.tw Tel: +886 - 7 - 8070166  
No.8-1, Pei-Lin Rd. Hsiao-Kang Dist., Kaohsiung, Taiwan Fax: +886 - 7 - 8071616