

Ding Zing® Film FS5180+PETP

Features

- Polyurethane polyester base
- Suitable for seam tape application
- With good adhesion not spoiling the original properties of carrier
- Good weathering properties
- Excellent UV stability

Physical Properties

*Properties	Unit	Method	Direction	**Value	Note
Hardness	Shore A	ASTM D2240		80 ±3	
Specific Gravity		ASTM D792		1.17	
Tensile Strength	Kg/cm ²	ASTM D882	MD	170	
			CD	172	
Elongation	%	ASTM D882	MD	805	
			CD	848	
300% Modulus	Kg/cm ²	ASTM D882	MD	45	
			CD	42	
Tear Strength	Kg/cm	ASTM D624	MD	58	
			CD	56	
Film Melting Point	°C			90	
UV stability	Grade	ASTM D1148		--	

**Actual results may yield up to ±15%.

*Data provided are used solely for references only, and are not guaranteed statements.



DING ZING CHEMICAL PRODUCTS CO., LTD.

SINCE 1981

http://www.dingzing.com e-mail: film@dingzing.com.tw Tel: +886 - 7 - 8070166
No.8-1, Pei-Lin Rd. Hsiao-Kang Dist., Kaohsiung, Taiwan Fax: +886 - 7 - 8071616