

Ding Zing[®] Film **FS80HT**

Features

- Polyurethane polyester base
- Transparent with smooth surface
- Easy for high frequency welding
- Good UV stabilization maintained after hydrolysis

Physical Properties

*Properties	Unit	Method	Direction	**Value	Note
Hardness	Shore A	ASTM D2240		82 ±3	
Specific Gravity		ASTM D792		1.20	
Tensile Strength	Kg/cm ²	ASTM D412	MD	284	
			CD	249	
Elongation	%	ASTM D412	MD	790	
			CD	872	
300% Modulus	Kg/cm ²	ASTM D412	MD	62	
			CD	56	
Tear Strength	Kg/cm	ASTM D624	MD	84	
			CD	87	
Film Melting Point	°C			120	
UV stability	Grade	D1148		4~5	

**Actual results may yield up to ±15%.

*Data provided are used solely for references only, and are not guaranteed statements.



DING ZING CHEMICAL PRODUCTS CO., LTD.

SINCE 1981

<http://www.dingzing.com> e-mail: film@dingzing.com.tw Tel: +886 - 7 - 8070166
No.8-1, Pei-Lin Rd. Hsiao-Kang Dist., Kaohsiung, Taiwan Fax: +886 - 7 - 8071616